

SHARPWORK

home
FAMILY
STUDY
favorites
download

:
 :
IP : 218.148.64.136
Login Join us

STUDY

&

IP

- , TAP 가 , PT, NPT	2006 - 02 - 28 09:42:46
: Sharp (218.*.242.254)	: 1975

- m/m (JIS)

	()		
		가	
1	0.25	0.2	
1.2	0.25	0.2	
1.4	0.25	0.2	0.3
1.6	0.35	0.2	
1.7	0.3	0.25, 0.2	0.35
1.8	0.35	0.2	
2	0.4	0.35, 0.25	
2.2	0.45	0.25	
2.3	0.4	0.35, 0.25	
2.5	0.45	0.35	
2.6	0.45	0.35, 0.25	
3	0.6	0.5, 0.35	
3.5	0.6	0.5	
4	0.7	0.5	0.75
4.5	0.75	0.75, 0.5	
5	0.8	0.75, 0.5	0.9
5.5	0.9	0.75, 0.5	
6	1	0.75, 0.5	
7	1	1, 0.75, 0.5	
8	1.25	1, 0.75, 0.5	
9	1.25	1.25, 1, 0.75, 0.5	
10	1.5	1.25, 1, 0.75, 0.5	
11	1.5	1.5, 1.25, 1, 0.75	
12	1.75	1.5, 1.25, 1, 0.75	
13	1.75	1.5, 1.25, 1, 0.75	
14	2	1.5, 1.25, 1, 0.75	
15	2	1.5, 1.25, 1, 0.75	
16	2	2, 1.5, 1.25, 1	
18	2.5	2, 1.5, 1.25, 1	
20	2.5	2, 1.5, 1.25, 1	

	()		
		가	
22	2.5	2, 1.5, 1.25, 1	
24	3	2.5, 2, 1.5, 1.25	
25	3	2, 1.5, 1	
26	3	2, 1.5, 1	
27	3	2.5, 2, 1.5, 1	
28	3	2, 1.5, 1	
30	3.5	3, 2, 1.5, 1	
32	3	2, 1.5, 1	
33	3.5	3, 2, 1.5, 1	
35	3	2, 1.5, 1	
36	4	3, 2, 1.5, 1	
38	4	3, 2, 1.5, 1	
39	4	3, 2, 1.5, 1	
40	3	2, 1.5, 1	
42	4.5	4, 3, 2, 1.5, 1	
45	4.5	4, 3, 2, 1.5	
46	1.5		
48	5	4, 3, 2, 1.5, 1	
50	5	4, 3, 2, 1.5, 1	
52	5	4, 3, 2, 1.5	
55	4	3, 2, 1.5	
56	5.5	4, 3, 2, 1.5	
58	4	3, 2, 1.5	
60	5.5	4, 3, 2, 1.5	
62	4	3, 2, 1.5	
64	6	4, 3, 2, 1.5	
65	4	3, 2, 1.5	
68	6	4, 3, 2, 1.5	
70	6	4, 2	

TAP 가 -

		100%	90%	85%
M1	0.25	0.73	0.76	0.77
M1.2	0.25	0.93	0.96	0.97
M1.4	0.3	1.08	1.11	1.12
M2	0.4	1.57	1.61	1.63
M2.5	0.45	2.01	2.06	2.09
M3	0.5	2.46	2.51	2.54
M3.5	0.6	2.85	2.92	2.95
M4	0.7	3.24	3.32	3.36
M4.5	0.75	2.69	3.77	3.81
M5	0.8	4.13	4.22	4.26
M6	1.0	4.92	5.03	5.08
M7	1.0	5.92	6.03	6.08
M8	1.25	6.65	6.78	6.85
M9	1.25	7.65	7.78	7.85
M10	1.5	8.38	8.54	8.62
M11	1.5	9.38	9.54	9.62
M12	1.75	10.1	10.3	10.4
M14	2.0	11.8	12.1	12.2
M16	2.0	13.8	14.1	14.2
M18	2.5	15.3	15.6	15.7
M20	2.5	17.3	17.6	17.7
M22	2.5	19.3	19.6	19.7
M24	3.0	20.8	21.1	21.2
M27	3.0	23.8	24.1	24.2
M30	3.5	26.2	26.6	26.8

(INCH)

	1 " (25.4m/m)		
	(UNC)	가	(UNF)

	1 " (25.4m/m)		
	(UNC)	가	(UNF)

TAP 가 -

		100%	90%	85%

No.1	64	72	9/32	20	28	No.1 - 64	1.854	64	1.42	1.47	1.49
2	56	64	5/16	18	24	2 - 56	2.184	56	1.69	1.74	1.77
3	48	56	3/8	16	24	3 - 48	2.515	56	1.94	2.00	2.03
4	40	44	7/16	14	20	4 - 40	2.845	40	2.16	2.23	2.26
5	40	44	1/2	12	13,20	5 - 40	3.175	40	2.49	2.56	2.59
6	32	40	9/16	12	18	6 - 32	3.505	32	2.65	2.73	2.77
8	32	36	5/8	11	18	8 - 32	4.166	32	3.31	3.39	3.44
10	24	32	3/4	10	11	10 - 24	4.862	24	3.68	3.79	3.85
12	24	28	7/8	9	14	12 - 24	5.486	24	4.34	4.45	4.51
1/16	60	64	1 "	8	12,14	1/4 - 20	6.350	20	4.98	5.11	5.18
3/32	48	56	1 1/8	7	12	5/16 - 18	7.938	18	6.41	6.56	6.64
1/8	40	44	1 1/4	7	12	3/8 - 16	9.525	16	7.81	7.98	8.06
9/64	40	44	1 5/16	7	12	7/16 - 14	11.12	14	9.1	9.3	9.4
5/32	32	36	1 3/8	6	12	1/2 - 13	12.700	13	10.6	10.8	10.9
11/64	40	36,32	1 1/2	6	12	9/16 - 12	14.288	12	12.0	12.2	12.3
3/16	24	28,32	1 5/8	5	12	5/8 - 11	15.875	11	13.4	13.6	13.8
7/32	24	28	1 3/4	5	12	3/4 - 10	19.050	10	16.3	16.6	16.7
15/64	24	28	2 "	4	12	7/8 - 9	22.225	9	19.5	19.5	19.6
1/4	20	28				1 " - 8	25.400	8	22.0	22.3	22.5

A : B : C : D(2) : E, F : B1 :

PT (R.RE)

PT ()

PS ()

PF ()


PS.PF (RP.G)

	JIS	ANSI		
W	SKH2	T1	SK	SK ,
	SKH3	T4	SKS	SKS
MO	SKH51	M2	HSS	
	SKH52	M3 - 1		
	SKH55	M35		
	SKH56	M36		
	SKH59	M42	HSS - CO	
	SKH58	M7	HSS	TAP
V	SKH53	M3 - 2	HSSE	EX - TAP
CPM	SKH10	T15	HSS	TAP


	PT	PF	PS
1/8 - 28	8.2	8.74	8.50
1/4 - 19	10.9	11.70	11.40
3/8 - 19	14.4	15.21	14.9
1/2 - 14	18.0	19.0	18.5
3/4 - 14	23.0	20.9	24.0
1 " - 11	29.0	24.5	30.0
1 1/4 - 11	38.0	28.2	39.0
1 1/2 - 11	44.0	30.7	45.0
2 " - 11	55.0	35.4	56.0

		PT(Rc)	PS(Rp)	PF(G)				PT(Rc)	PS(Rp)	PF(G)	
1/16~28	7.312	O	-	-	10.1	1 1/14~11	41.910	O	O	O	10.1
1/8~28	9.728	O	O	O	13	1 3/8~11	44.323	O	-	-	13
1/4~19	13.157	O	O	O	21	1 1/2~11	47.803	O	O	O	21
3/8~19	16.662	O	O	O	21	1 5/8~11	51.990	O	O	O	21
1/2~14	20.955	O	O	O	25	1 3/4~11	53.746	O	O	O	25
5/8~14	22.911	O	O	O	25	2 " ~11	59.614	O	O	O	25
3/4~14	26.441	O	O	O	25	2 1/2~11	75.184	O	O	O	25
7/8~14	30.201	O	-	O	28	3 " ~11	87.884	O	O	O	28
1 " ~11	33.249	O	O	O	32	3 1/2~11	100.330	O	O	O	32
1 1/8~11	37.897	O	-	O	32	4 " ~11	113.030	O	O	O	32

NPT



NPTF



NPT ()

(U.S.A)
가 60°
1/16

NPS ()

(U.S.A)
가 60°

NPTF ()

NPT , 가

NPSF ()

NPS , 가

	NPT	NPS
1/8 - 27	8.61	8.74
1/4 - 18	11.13	11.28
3/8 - 18	14.68	14.68
1/2 - 14	17.86	18.26
3/4 - 14	23.42	23.42
1 " - 11 1/2	29.36	29.36
1 1/4 - 11 1/2	38.10	38.10
1 1/2 - 11 1/2	44.04	44.45
2 " - 11 1/2	56.36	56.36

		NPT	NPS	NPTF	NPSF				NPT	NPS	NPTF	NPSF	
1/16~27	7.142	O	O	O	O	12	1 1/4~11	40.218	O	O	O	O	28.1
1/8~27	9.489	O	O	O	O	12.05	1 3/8~11	46.287	O	O	O	O	28.4
1/4~18	12.487	O	O	O	O	17.45	1 1/2~11	58.325	O	O	O	-	28
3/8~18	15.926	O	O	O	O	17.65	1 5/8~11	70.159	O	O	-	-	40.8
1/2~14	19.772	O	O	O	O	22.85	1 3/4~11	86.068	O	O	-	-	42.95
3/4~14	25.117	O	O	O	O	22.95	2 " ~11	98.776	O	O	-	-	44.7
1 " ~11 1/2	31.461	O	O	O	O	27.4	2 1/2~11	111.433	O	O	-	-	45.55

리스트

57

No	Title	Name	Date	Hits
57	- , HOT	Sharp	06 - 10 - 11	745
56	General Chemical Resistance Guide() HOT	Sharp	06 - 08 - 29	775
55	(stainless steel) HOT	Sharp	06 - 08 - 29	851
54	HOT	Sharp	06 - 08 - 29	767
53	F HOT	Sharp	06 - 08 - 29	693
52	/ / HOT	Sharp	06 - 08 - 29	660
51	Teflon() PTFE, FEP, PFA, PVDF F HOT	Sharp	06 - 07 - 07	814
50	NPSH(Net Positive Suction Head) HOT	Sharp	06 - 06 - 23	824
49	ISA codes for Process Instrumentation HOT	Sharp	06 - 05 - 23	674
48	F HOT	Sharp	06 - 05 - 09	645
47	Calibration pot(,) - STS304 F HOT	Sharp	06 - 03 - 20	727
46	- , TAP 가 , PT, NPT HOT	Sharp	06 - 02 - 28	1975
45	(fitting) - NPT, PT, PF HOT	Sharp	06 - 02 - 16	1513
44	LG 6.4" TFT LCD(LB064V02 - B1) F HOT	Sharp	06 - 01 - 13	757
43	, , F HOT	Sharp	05 - 12 - 26	1140

1 2 3 4